

# CD7-V Series

(KCD71VUG)

## Data Center NVMe™ Mixed-use SSD

The CD7-V 2.5-inch form factor Series is a mixed-use data center NVMe™ SSD that is optimized to support a broad range of scale-out and cloud applications, including big data/ IoT, online transaction processing and virtualization. Built with a PCIe® 4.0 (16 GT/s x4) interface, the CD7-V 2.5-inch form factor Series SSDs deliver consistent performance up to 1,100K IOPS (random read) and 375K IOPS (random write), with active power consumption of 11-19 W.

Featuring KIOXIA 96-layer BiCS FLASH™ 3D TLC memory, CD7-V 2.5-inch form factor SSDs deliver 3DWPD (Drive Writes Per Day) of endurance and storage capacities up to 12.8 TB in a 2.5-inch form factor, making them well-suited for hyperscale data center applications.



Product image may differ from the actual product.

## Key Features

- PCIe® 4.0, NVMe™ 1.4 specification compliant
- Form factor: 2.5-inch, 15mm Z-height
- Proprietary KIOXIA architecture: controller, firmware and 96-layer BiCS FLASH™ 3D TLC
- Single-port design, optimized for data center class workloads
- Consistent performance and reliability for demanding 24x7 environments
- Designed for high-density storage deployments
- Power loss protection (PLP) and end-to-end data correction

## Key Applications

- Hyperscale
- IoT and big data analytics
- Online transaction processing (OLTP) (transactional and relational databases)
- Virtualized environments
- Streaming media and content delivery networks

## Specifications

Base Model Number	KCD71VUG12T8	KCD71VUG6T40	KCD71VUG3T20	KCD71VUG1T60	KCD71VUG800G
Capacity	12,800 GB	6,400 GB	3,200 GB	1,600 GB	800 GB
<b>Basic Specifications</b>					
Interface	PCIe® 4.0, NVMe™ 1.4				
Maximum Interface Speed	64 GT/s (Gen4 x4)				
Flash Memory Type	BiCS FLASH™ TLC				
<b>Performance in single port (x4) mode (Up to)</b>					
Sustained 128 KiB Sequential Read	6,450 MB/s		6,650 MB/s		6,250 MB/s
Sustained 128 KiB Sequential Write	5,600 MB/s		3,200 MB/s	3,600 MB/s	1,700 MB/s
Sustained 4 KiB Random Read	1,100 K IOPS				850 K IOPS
Sustained 4 KiB Random Write	370 K IOPS	375 K IOPS	330 K IOPS	355 K IOPS	140 K IOPS

## Specifications (Continued)

Capacity	12,800 GB	6,400 GB	3,200 GB	1,600 GB	800 GB
<b>Power Requirements</b>					
Supply Voltage	12 V ± 10 %, 3.3 V ± 15 %				
Power Consumption (Active)	19 W Typ.	18 W typ.	13 W typ.		11 W typ.
Power Consumption (Ready)	5 W typ.				
<b>Reliability</b>					
MTTF	2,500,000 hours				
Warranty	5 years				
DWPD	3				
<b>Dimensions</b>					
Height	15 mm + 0, - 0.5 mm				
Width	69.85 ± 0.25 mm				
Length	100.45 mm Max				
Weight	150 g Max				
<b>Environmental</b>					
Temperature (Operating)	0 °C to 70 °C				
Temperature (Non-operating)	-40 °C to 80 °C				
Humidity (Operating)	5 % to 95 % R.H.				
Vibration (Operating)	21.27 m/s <sup>2</sup> { 2.17 G } ( Peak, 5 to 800 Hz )				
Shock (Operating)	9.8 km/s <sup>2</sup> { 1,000 G } ( 0.5 ms )				

Definition of capacity: KIOXIA Corporation defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2<sup>30</sup> = 1,073,741,824 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

GT/s: Giga Transfers per second.

A kibibyte (KiB) means 2<sup>10</sup>, or 1,024 bytes.

MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

DWPD: Drive Write Per Day. One full drive write per day means the drive can be written and re-written to full capacity once a day every day for the specified lifetime. Actual results may vary due to system configuration, usage and other factors.

Read and write speed may vary depending on various factors such as host devices, software (drivers, OS etc.), and read/write conditions.

IOPS: Input Output Per Second (or the number of I/O operations per second).

CD7-V Series does not support security function.

\*PCIe is a registered trademark of PCI-SIG.

\*NVMe is a registered or unregistered mark of NVM Express, Inc. in the United States and other countries.

\*All other company names, product names, and service names may be trademarks of their respective companies.